Journal of Indian Water Works Association Vol. XXXXIV DODDDDD No. 30000 July-September 2012

Sustainable Urban Water Management Systems: A Review of Status with focus on Surat city of Gujarat state in India

Mrs.Reena Popawala¹, Dr. N C Shah²

Abstract

Abstract Research efforts in recent years have been made on water and waste water technologies and management. However, there is need to clarify and define urban water management systems and how to manage if or achieving usatianbility. Sustainable development is social and economic prosperity while protecting natural systems. Many recent efforts have been undertaken to transfer knowledge from the developed to the developing nations to achieve new sustainable thrane. This paper aims to present the concept and approach of sustainable development for urban water management with recommendations for future efforts. It includes literatore review of sustainable urban water management systems, gaps of urban water management and identifies potential approach for sustainable urban water management focusing on Swart city of Guparts state in India. The collected data and analysis represents that arban water management is not only concerned with functional management of the system should transform from a reactive approach to proactive approach and from end of pipe solution to close loop system.

Asst. Prof. in Civil Engineering Department C.K.Pithawalla College of Engg. & Tech., Surat
 Prof. of CED & Section Head (TEP) SVNIT, Surat, India

Journal of Indian Water Works Association 185

BACKGROUND :

In 1992, Intertaining conference on water and environment was held at Dublin. They issued four guiding principles regarding water, [10] is importance as a finite and vulnerable resource, essential to sustain life, development and the environment, [2] the management should be based on participatory approach, [3] the importance of worman's role, [4] water is an economic good, in all its competing uses⁴.

In 2000, Millennium Development Goals stated • eight major goals for the year 2015 horizon, including poverty reduction, health improvements and sustainable development targets.

In the year 2002, World summit on sustainable development, Johanneaburg, added a target to the MDG for halving the number of people without safe access to drinking water and included a commitment for the development of integrated water management².

The year 2005 was launched as "Water for Life" * decade to promote the efforts in the field of water targeting the horizon 2015.

The year 2006, fourth world water forum, Mexico published a guideline regarding water issue and target is to achieve environmental sustainability and • protection⁸.

mal of Indian Water Works Association 186

In the downstream of weir in river Tapi, due to tidal influences river water becomes brackish.

As a result at the beginning of year 2007, many water related success and failure stories are available.

July-September 2012

STODI AREA: Some issues related to Surat city are narrated which need immediate attention for sustainable urban water management.

sanagement. Surat city has perennial river Tapi, but local government can extract only 700 MLD (Million liters per day) of water daily from river Tapi according to riparian right, which is not sufficient to fulfill the demand of citizen and high growth rate of population.

The of population. Of Veir cum cause way on inver Tapi, a reservoir is formed on upstream side of river, which led to stagnation of flowing river water. Stagnation of water gives rise to growth of algae and weed, hence raw water quality gets degraded.


Moreover, a sewage discharge fron Kosad, Amreli, Motta Varraccha, created terrible impact on river v upstream of river ha, and Kathor has

.

Recently, it was decided to lay down pipelines from Ukai to Surat (100 km) to resolve the issues regarding quality and quantity of water supply demand as a suggestion in revised city development plan. The question is, will this decision conomically viable or sustainable?

July-September 2012

Written by Administrator Wednesday, 17 April 2013 08:52 - Last Updated Tuesday, 23 April 2013 09:27



Owing to these problems the bore water of adjacent area like Rander, Athwa, and Old walled city area becomes salty and not fit for drinking. Over withdrawal of ground water for industrial and irrigation purpose has depleted the ground water table and degraded the quality of ground

Total population of city is not covered by easy access to water supply and sanitation system. Whole city area is also not covered with storm water drainage system. Rainwater recharging/ harvesing systems are not implemented on large scale. Most of the water connections are without

183



4. METHODOLOGY: The study involves compilation, review and comparison of information with threshold value on urban water management and recommending potential approaches to achieve sustainability. It consists of following actions of the state of the st appr ing steps

- First step involves review of the fit concept focusing on sustainable un management as background study. urban water
- An approach of sustainable development in urban water management system is proposed by aiming to answer the following questions: What are the requirements of sustainable urban water management? Which parameters should be considered as measure of sustainability? And what are the approaches used in past experiences. 2)
- Third step focuses on review of indicator for assessing urban water management systems and selected indicator for identifying the status of urban water management system.
- aurth step involves review and co ta regarding the urban water ma sess sustainability performance.
- Fifth step involves assessment of existing situation by comparing with threshold value. The results obtained from this step are the identification of gap in urban water management towards sustainability.
- The recommendations on possible approaches for sustainable urban water management in the city are based on the gaps and selected approaches that are expected to suit the overall condition of the region. The recommendation

SYSTEM BOUNDARY FOR URBAN WATER MANAGEMENT SYSTEM: System boundary is decided based on systematic consideration of the various dimensions of water.

Domain of system boundary consists of water supply system, waste water, storm water, rain water recharging/harvesting & its sub criteria. Sustainability is related to prolonged time perspectives hence it should be selected accordingly.

Journal of Indian Water Works Association

Raw water with drawl Distribution Use Waste water collection nent - Reuse e treatment Land fill Ra R recharging

July-September 2012

Fig 2 St dery for Fig.2 System beandary for urban water management SELECTION OF INDICATOR AND CRITERIA: CITIERIA selection involved the selection of appropriate criteria for the field of research given their relevance to current issues, their appropriateness to the area in question, their scientific and analytical basis plus their ability to effectively present the issues they are designed for. Theoretical framework building provides the underlying basis for criteria selection and snapported the overall structure of them wate management. The foor dimensional view on stantiability was employed, and these four ensuring the selection of the proposed framework the ensuring the structure of the selection of the selection of the ensuring the selection of the selection of the selection of the ensuring the selection of the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the ensurement of ourismic the selection of the selection of the selection of the ensurement of ourismic the selection of the selection of the selection of the ensurement of ourismic the selection of the selection

DATA COLLECTION:

DATA COLLECTION: The data were collected related to the criteria and indicators which were selected for the study. This includes data related to social, economic, environmental and engineering factors and its sub factor like population seved by water supply and wate water system, storm water, capital investment, economic expenditure and maintenne, water supply per capita per day, waste water generation per capita

188

July-September 2012

Written by Administrator Wednesday, 17 April 2013 08:52 - Last Updated Tuesday, 23 April 2013 09:27

Municipal Corporation. The data collection w difficult task. The ground water monitoring are available in the out skirts of the city (or wells) but within the city limit no wells are av hence, the data related to decrease in ground table were skipped, though it was very im parameter. per day, area covered under pipe network consumption, cost recovery, revenue collect water supply, sewerage system, flood prone from Surat Municipal Corporation (SMC). n from ea etc.


All data related to studies are collected from hydraulic and drainage department of Surat
 Sr.
 Criteria
 Sub criteria
 Threshold

| Sr. No | Criteria | Sub criteria | Threshold Value | Existing Status |
|-----------|---------------|---|---|--|
| 1 | Social | Access to water supply | 100% population should catered | 56% |
| | | Access to sanitation | 100% population should catered | 30% |
| | | Water availability/capita/day | According to WHO for domestic supply 135 lpcd | 195 LPCD |
| | | Supply hours | 24 x 7 hours | 3 hrs |
| | | Service complaints | As low as possible | 350 complaints/ year |
| | | Flood prone area | Minimum | 250 |
| 2. | Economic | Capital investment | Payback period Should be minimum | Payback period is minimum |
| | | Cost recovery and maintenance | 100% Cost should be recovered | 99% |
| | | Research and development fund | At least 10-15% fund should available | No fund for R & D |
| 3. | Environmental | Water withdrawal | Less than 100% of available quantity | 100% water withdrawal from surface water source |
| | | Energy consumption | Maximum renewable energy source should be utilized | Energy used is generated from fossil fuel |
| | - | Pollution load on environment | Minimum load | |
| | | Wastewater treatment performance | Within the standards laid by WHO | Within the standards laid by WHO |
| | | Water reuse | 100% should be reused | Not reused |
| | | Recycling of nutrient and sludge | 100% should be utilized | Not utilised |
| | | Strom water area covered under piped network | 100% area should be covered | 45% |
| | | Rain water recharging/ harvesting | 100% area should be covered | 0.05 % |
| | 11 | Salinity ingress | As low as possible | - |
| 4. | Engineering | Metered connection | 100% area should be covered | 0.41% |
| 1 | | Service interruption and water losses | As low as possible | Approximately 30% |

Journal of Indian Water Works Association 189

% no

July-September 2012 ation covered after extension of city



Area covered under pipe network after extension of city limit

| | | | | | **** | |
|------------------------------|------|------|------|------|------|------|
| | | | | | | |
| | | | | | | |
| | | - | | | | |
| | | | | | | |
| 1 | | | - | | | |
| | | | ~ | | | |
| | | | ~ | | | |
| years | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 |
| years •original situation | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 |

190

5. CONCLUSION: study reveals that, the shold value and existing ria. For improvement

and for modeling of pipe failure or le This will minimize the water losses water can be utilized to serve more sting situation in engineering ent in the UWM system it is install metered connection in ounted for water results both tal criteria sh

Envir impro rechar ed connection in ater results both Along with that set management ed by ing ging and harvesti ngof

Journal of Indian Water Works Association


a. Ui

ere is large gap be

onnections ection of a

mber 2012 July-Septe

Written by Administrator Wednesday, 17 April 2013 08:52 - Last Updated Tuesday, 23 April 2013 09:27



Others : 3% ure in

tributes 66% of total water management cost so, an be reduced to some extent by implementing rgy efficient technique or renewable energy rces should be used. e study of social criteria reveals that whole a is not covered with water supply and dra works oi it is essential to complete the netwo same time per capita water consumption is l in the basic need which represents that due to findarticuture facility people are not getting ply in some of the area. Majorly this happe


The

Fig. 6 Opt

extension of city limit in year 2003. There is hugge ariation between area covered under pipe network t percentage population covered before & after txtension of city limit. This is because of transition age of extension of city limit. It takes time foot stablishing infrastructure facilities which represents & perc inage rk. At a drop in po amption is higher is that due to lack ow away to replace water n due

Joi al of Indian Water Works Asso 191 July-Septer ber 2012





ACKNOWLEDGEMENT: United Nations: 34, UN (2005) World Population Prospects: the 2004 Revi population Database. UNPP (2004) Web site: http:/ un.org/umpp/(October 2006) Nitirach Sa-nguanduan and Vilas Nitivattana "Sustainable urban water management system: Retion of ^{2.} 70020 1. the 2004 Revision 4) Web site: http://csa. This project has been funded by The Institutio Engineers (India), 8, Gokhale Road, Kolkata 7(under R & D Grant- in -aid scheme 2010-2011. 3. REFERENCES: 1. The Millennium De of st Wor ist Asian counts ent Goals Report, New York, 4. cus on sou ion on Enrld Ce

Journal of Indian Water Works Association July-September 2012 192

Written by Administrator Wednesday, 17 April 2013 08:52 - Last Updated Tuesday, 23 April 2013 09:27

